



The newly designed dual lock connector provides universal locking with a clean and functional twist locking mechanism engineered into the cord grip body. Perfect for any installation.

Fit: Universal

HOW IT WORKS

SPECIFICATIONS	DESCRIPTION
STANDARD	IEC 60320
HIGH TEST VOLTAGE	2000VAC (1MIN 50Hz) 500VDC (1MIN)
RATING	UL/cUL: 10A/13A/15A 250VAC TUV or VDE: 10A 250VAC
OPERATIONAL TEMP	-25°C~ 70°C
FLAMABILITY	PLUG/CONNECTOR: UL 94-V CABLE: UL VW-1, IEC60332-1. CAT F2
CONDUCTOR SIZE	NORTH AMERICA: 18AWG/16AWG/14AWG EUROPE: 0.75MM2/1.0MM2

ORDERING

S-LOCK
CONFIGURATION



1413S - X - XXX - XXX

WIRE	CLASSIFICATION
18AWG/SVT	SVT
18AWG/SJT	F
16AWG/SJT	G
14AWG/SJT	H
0.75MM2 H05VV-F	00
1.00MM2 H05VV-F	01

LENGTH (INCHES)
*lengths in FT are
stocked

*BLACK IS STANDARD

GRY
BLU
PUR
GRN
ORG
RED
YEL
WHT

