


STANDARDS	IEC 60320 <input checked="" type="checkbox"/>
APPROVALS	C-UL <input checked="" type="checkbox"/> UL <input checked="" type="checkbox"/>
CERTIFICATIONS	ROHS <input checked="" type="checkbox"/>



IEC 60320, C20  
(ROTATED 90°)

IEC 60320, C19  
(ROTATED 90°)

**SPECIFICATIONS:**

- OVERALL LENGTH: 4572 ± 50 mm (180 INCHES)
- CONDUCTORS: 12awg-3c
- JACKET: SJT(OW), 105°C, GREEN
- PLUG: IEC 60320 C20, STRAIGHT, GREEN
- CONNECTOR: IEC 60320 C19, STRAIGHT, GREEN
- RATED: 20A 250V
- PUT-UP: COILED
- WEIGHT (APPROX): 1.8 LBS / 0.82 Kg
- MISCELLANEOUS:

**WORLD CORD SETS, INC.**

TEL (860)763-2100  
FAX (860)763-1183



www.WorldCordSets.com  
sales@WorldCordSets.com

TITLE  
IEC 60320 C20 to C19 DETACHABLE POWER CORD

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE NONE	DATE 12-06-2012	PART NO. 2019-J-180-GRN	REV -
---------------	--------------------	----------------------------	----------