

Description	User Attachable GFCI, In-Line Style
Rated Current	13 amps
Rated Supply Voltage	125 Volts
Frequency	60 Hz
Polarity	2 Pole 3 Wire
Tripping Current	4-6 mA
Maximum Tripping Time	25 ms
Ambient Temperature Range	-35C to 66C
Reset Type upon Power Loss	Automatic (also known as Passive or Latching)
Color	Black
Design	UL Standard 943 Class A
	UL Listed
	Rainproof Design
Cordage	Accepts 16/3 awg SJT(W)
Grommet	for 16/3 awg cordage
Function	Test and Reset Buttons not to be used as ON/OFF switch

## ALL DIMENSIONS ARE IN MILLIMETERS

## WORLD CORD SETS, INC.

TEL (860)763-2100 FAX (860)763-1183



www.WorldCordSets.com sales@WorldCordSets.com

TITLE

GFCI, USER ATTACHABLE, IN-LINE STYLE

RD SETS. SCALE NONE

DATE 12-3-2007 PART NO. IL-A-13125

REV

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.