





STANDARDS	IEC 60320 <input checked="" type="checkbox"/>
APPROVALS	UL <input checked="" type="checkbox"/>
CERTIFICATIONS	ROHS <input checked="" type="checkbox"/>



IEC 60320, C14



RELEASE BUTTON



IEC 60320, C13  
LOCKING

SPECIFICATIONS:

- 1. OVERALL LENGTH: 4572 ± 50 mm (180 INCHES)
- 2. CONDUCTORS: 18awg-3c
- 3. JACKET: SJT BLACK
- 4. PLUG: IEC 60320 C14, BLACK
- 5. CONNECTOR: IEC 60320 C13 LOCKING, BLACK
- 6. RATED: 10 AMPERE 250 VOLT
- 7. PUT-UP: COILED
- 8. WEIGHT (APPROX): 1.1 LBS / 0.5 Kg
- 9. MISCELLANEOUS:

**WORLD CORD SETS, INC.**

TEL (860)763-2100            www.WorldCordSets.com  
 FAX (860)763-1183      sales@WorldCordSets.com

TITLE  
C14 to C13 LOCKING

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE NONE	DATE 02-16-2016	PART NO. <b>1413K-F-180</b>	REV —
---------------	--------------------	--------------------------------	----------