


STANDARDS	IEC 60320 ☒
APPROVALS	C-UL ☒ UL ☒
CERTIFICATIONS	ROHS ☒



IEC 60320, C20
(ROTATED 90°)

IEC 60320, C19
(ROTATED 90°)

SPECIFICATIONS:

- OVERALL LENGTH: 2438 ± 50 mm (96 INCHES)
- CONDUCTORS: 12awg-3c
- JACKET: SJT(OW), 105°C, GREEN
- PLUG: IEC 60320 C20, STRAIGHT, BLACK
- CONNECTOR: IEC 60320 C19, STRAIGHT, BLACK
- RATED: 20A 250V
- PUT-UP: COILED
- WEIGHT (APPROX): 1.20 LBS / 0.55 Kg
- MISCELLANEOUS:

WORLD CORD SETS, INC.

TEL (860)763-2100
FAX (860)763-1183



www.WorldCordSets.com
sales@WorldCordSets.com

TITLE

IEC 60320 C20 to C19 DETACHABLE POWER CORD

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS.
NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE
NONE

DATE
12-06-2012

PART NO.
2019-J-096.030

REV
—