




STANDARDS	IEC 60320 <input checked="" type="checkbox"/>
APPROVALS	UL <input checked="" type="checkbox"/>
CERTIFICATIONS	ROHS <input checked="" type="checkbox"/>



IEC 60320, C14



RELEASE BUTTON



IEC 60320, C13
LOCKING

SPECIFICATIONS:

1. OVERALL LENGTH: 914 ± 20 mm (36 INCHES)
2. CONDUCTORS: 18awg-3c
3. JACKET: SJT RED
4. PLUG: IEC 60320 C14, RED
5. CONNECTOR: IEC 60320 C13 LOCKING, RED
6. RATED: 10 AMPERE 250 VOLT
7. PUT-UP: COILED
8. WEIGHT (APPROX): 0.28 LBS / 0.13 Kg
9. MISCELLANEOUS:

WORLD CORD SETS, INC.

TEL (860)763-2100
FAX (860)763-1183



www.WorldCordSets.com
sales@WorldCordSets.com

TITLE

C14 to C13 LOCKING

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE
NONE

DATE
02-16-2016

PART NO.
1413K-F-036-RED

REV
—