





STANDARDS	IEC 60320 <input checked="" type="checkbox"/> NEMA 5-15P <input checked="" type="checkbox"/>
APPROVALS	UL <input checked="" type="checkbox"/> C-UL <input checked="" type="checkbox"/>
CERTIFICATIONS	ROHS <input checked="" type="checkbox"/>



NEMA 5-15P



IEC 60320, C13
LOCKING

SPECIFICATIONS:

1. OVERALL LENGTH: 1829 ± 50 mm (72 INCHES)
2. CONDUCTORS: 14awg-3c
3. JACKET: SJT BLACK
4. PLUG: NEMA 5-15P, STRAIGHT, BLACK
5. CONNECTOR: IEC 60320 C13 LOCKING, STRAIGHT, BLACK
6. RATED: 15 AMPERE 125 VOLT
7. PUT-UP: COILED
8. WEIGHT (APPROX): 0.65 LBS / 0.3 Kg
9. MISCELLANEOUS:

WORLD CORD SETS, INC.

TEL (860)763-2100
FAX (860)763-1183



www.WorldCordSets.com
sales@WorldCordSets.com

TITLE

NEMA 5-15P to C13 LOCKING

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE
NONE

DATE
06-14-2013

PART NO.
51513K-H-072

REV
—