



|                |                                                                                |
|----------------|--------------------------------------------------------------------------------|
| STANDARDS      | IEC 60320 <input checked="" type="checkbox"/>                                  |
| APPROVALS      | CSA <input checked="" type="checkbox"/> UL <input checked="" type="checkbox"/> |
| CERTIFICATIONS | ROHS <input checked="" type="checkbox"/>                                       |



IEC 60320  
LOCKING C20

IEC 60320, C13

SPECIFICATIONS:

1. OVERALL LENGTH: 6 FEET
2. CONDUCTORS: 14awg-3c
3. JACKET: SJT, RED
4. PLUG: IEC 60320 C20 LOCKING, STRAIGHT, RED
5. CONNECTOR: IEC 60320 C13, STRAIGHT, RED
6. RATED: 15 AMPERE 250 VOLT
7. PUT-UP: COILED
8. WEIGHT (APPROX): 0.73 LBS / 0.33
9. MISCELLANEOUS:

**WORLD CORD SETS, INC.**

TEL (860)763-2100  
FAX (860)763-1183



www.WorldCordSets.com  
sales@WorldCordSets.com

TITLE

LOCKING C-20 TO C-13 15A 250V POWER CORD

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS.  
NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE  
NONE

DATE  
07-08-2015

PART NO.  
**20K13-H-072-RED**

REV  
—