


STANDARDS	IEC 60320 <input checked="" type="checkbox"/>
APPROVALS	UL <input checked="" type="checkbox"/> C-UL <input checked="" type="checkbox"/>
CERTIFICATIONS	ROHS <input checked="" type="checkbox"/>



IEC 60320, C14
(ROTATED 90°)

IEC 60320, C19
(ROTATED 90°)

SPECIFICATIONS:

1. OVERALL LENGTH: 1000 ± 50 mm (39 INCHES)
2. CONDUCTORS: 14 AWG x 3, NACC
3. JACKET: SJTOW, 105°C, BLACK
4. PLUG: IEC 60320 C14, STRAIGHT, BLACK
5. CONNECTOR: IEC 60320 C19, STRAIGHT, BLACK
6. RATED: 15 AMPERE 250 VOLT
7. PUT-UP: BULK PACKED
8. WEIGHT (APPROX): 0.48 LBS / 0.22 Kg
9. MISCELLANEOUS:

WORLD CORD SETS, INC.

TEL (860)763-2100
FAX (860)763-1183



www.WorldCordSets.com
sales@WorldCordSets.com

TITLE

C14 C19 DETACHABLE POWER CORD

THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN ARE THE PROPRIETARY CONFIDENTIAL PROPERTY OF WORLD CORD SETS. NO USE OR REPRODUCTION IN PART OR WHOLE MAY BE MADE WITHOUT WRITTEN PERMISSION FROM WORLD CORD SETS.

SCALE
NONE

DATE
07-15-2010

PART NO.
1419-H-039

REV
-