

ZH15-2019-157-BLK

4m C20 to C19 1.5mm² LSZH BLACK Cordage



FEATURES / BENEFITS

- Plug Type: IEC 60320 C20. The IEC 60320 C20 is a grounded 3 Wire Plug rated up to 250V and 20 Amps. The C20 mates with a C19 outlet, typically found on Data Center/IT specific PDUs (Power Distribution Unit). The most common configuration for a C20 is in a jumper cable scenario, providing power from a PDU to a blade server chassis, high powered server, large network router, or similar device.
- Connector Type: IEC 60320 C19. The IEC 60320 C19 is a grounded 3 Wire connector rated up to 250V and 20 Amps. The C19 mates with a C20 inlet, and is commonly used in a jumper cable scenario in IT Installations providing power from a PDU to a server, router, switch or other computing device. The C19 is typically used in high powered blade server chassis, large network routers, and other IT equipment that draws more power than a standard C13 can accommodate.

-
-



SPECIFICATIONS

Product Weight	~1.05 lbs.
Shipping Volume	~130.6 in ³
Length	4.0 meters
Current (Amps)	15 Amps
Voltage (Volts)	250 volts
Connector (Female)	IEC 60320 C19
Plug (Male)	IEC 60320 C20
Cordage	1.5mm ² LSZH
Certifications	RoHS
Country of Origin	USA
Color	Black