



World Cord Sets, Inc.

(860) 763-2100

[sales@worldcordsets.com](mailto:sales@worldcordsets.com)

<https://shop.worldcordsets.com/shop>



## ZH10-1413-024-BLK

2FT C13 C14 1.0mm<sup>2</sup> LSZH BLACK Power Cord



IEC 60320 C14 C13 Power Cords utilizing LOW SMOKE ZERO HALOGEN cordage (BSI, HAR, ROHS, IEC, HD21.14, BS EN 50525-3-11). For installation where fire, smoke emission, and toxic fumes create a potential threat to life and equipment. Common abbreviations for Low Smoke Zero Halogen are LSZH, LS0H, LSOH, LSFH, 0HLS, OHLS. This 2 FT C14 C13 LSZH power cord can be used in data centers to help protect against damage to humans and equipment in case of fire. Typically used to connect a PDU to a server, router, or switch.

## Product Specifications

Color	Black
Current (Amps)	10 Amps
Voltage (Volts)	250 volts
Connector (Female)	 IEC 60320 C13
Plug (Male)	 IEC 60320 C14
Country of Origin	USA
Cordage	1.0mm <sup>2</sup> LSZH
Length	2 Feet

## Typical Applications for IEC 60320 C13 to C14 Power Cords

Below is one the typical applications of a C13 to C14 power cord connecting a Rack Mount PDU (Power Distribution Unit) to a Server, Router, or Switch. This scenario is extremely common in data center environments and in enterprise networking rooms.

